



# Keymer Goxhill

## Product Technical Information Sheet

ROOF TILING	
Material	Clay
Minimum roof pitch	35°
Headlap (minimum)	65mm
Batten spacing at fixed gauge <sup>1</sup>	100mm
Size of tile <sup>1</sup>	265 x 165mm
Covering capacity	60 tiles per m <sup>2</sup>
Cover width	165mm
Profile depth	16mm
Hanging length	249mm
Weight as laid	72.2 kg per m <sup>2</sup>
Weight per tile	1.202 kg
Weight per pallet	0.694 tonnes
Bond	Cross / Broken
Quantity per pallet	530
Battens per m <sup>2</sup>	10m
Batten size -	38 x 25mm
Nail size/type for tiles	38 x 3.35 mm aluminium ring shank clout head
VERTICAL TILING	
Minimum roof pitch	75°
Headlap (minimum)	38mm
Batten spacing at fixed gauge <sup>1</sup>	114mm
Size of tile <sup>1</sup>	265 x 165mm
Covering capacity	53 tiles per m <sup>2</sup>
Cover width	165mm
Profile depth	16mm
Hanging length	245mm
Weight as laid	63.7kg per m <sup>2</sup>
Weight per tile	1.202 kg
Bond	Cross / Broken
Quantity per pallet	530
Battens per m <sup>2</sup>	8.8m
Batten size	38 x 25mm
Nail size/type for tiles	38 x 3.35 mm aluminium ring shank clout head



<sup>1</sup> Clay tiles are subject to small variations in size because of drying and firing shrinkage in the manufacturing process. Before deciding on the batten gauge and linear coverage, the roof tiler should inspect each batch of tiles to ensure that the correct minimum headlap and sidelap are achieved. Unless otherwise stated, data is based on the tiles laid at minimum headlap.

**Tile Fixing** - For information please contact the Keymer team.

**e.** info@keymer.co.uk  
**t.** 01427 871200  
**w.** keymer.co.uk