



# Keymer Kent Peg Tile

## Product Technical Information Sheet

Material	Clay
Minimum roof pitch	40°
Headlap	60mm
Batten spacing at fixed gauge <sup>1</sup>	95mm
Size of tile <sup>1</sup>	250 x 150mm
Covering capacity	70.2 tiles per m <sup>2</sup>
Cover width	150mm
Profile depth	13mm
Hanging length	230mm
Weight as laid	84.3kg per m <sup>2</sup>
Weight per tile	1.2kg
Weight per pallet (including pallet & packaging)	0.989 tonnes
Bond	Cross / Broken
Quantity per pallet	800
Battens per m <sup>2</sup>	10.6m
Batten size - up to 600mm rafter centres	38 x 25mm
Nail size/type for tiles	Fix with oak or aluminium pegs



<sup>1</sup> Clay tiles are subject to small variations in size because of drying and firing shrinkage in the manufacturing process. Before deciding on the batten gauge and linear coverage, the roof tiler should inspect each batch of tiles to ensure that the correct minimum headlap and sidelap are achieved. Unless otherwise stated, data is based on the tiles laid at minimum headlap.

**Tile Fixing** - For information please contact the Keymer team.

**e.** [info@keymer.co.uk](mailto:info@keymer.co.uk)

**t.** 01427 871200

**w.** [keymer.co.uk](http://keymer.co.uk)