



Keymer Shire

Product Technical Information Sheet

ROOF TILING

Material	Clay
Minimum roof pitch	40°
Headlap (minimum)	65mm
Batten spacing at fixed gauge ¹	100mm
Size of tile ¹	265 x 165mm
Covering capacity	60 tiles per m ²
Cover width	165mm
Profile depth	13mm
Hanging length	245mm
Weight as laid	73.2 kg per m ²
Weight per tile	1.22 kg
Weight per pallet	0.715 tonnes
Bond	Cross / Broken
Quantity per pallet	550
Battens per m ²	10m
Batten size -	38 x 25mm
Nail size/type for tiles	38 x 3.35 mm aluminium ring shank clout head

VERTICAL TILING

Minimum roof pitch	75°
Headlap (minimum)	38mm
Batten spacing at fixed gauge ¹	114mm
Size of tile ¹	265 x 165mm
Covering capacity	53 tiles per m ²
Cover width	165mm
Profile depth	13mm
Hanging length	245mm
Weight as laid	
Weight per tile	1.22 kg
Weight per 1000	
Bond	Cross / Broken
Quantity per pallet	550
Battens per m ²	8.8m
Batten size	38 x 25mm
Nail size/type for tiles	38 x 3.35 mm aluminium ring shank clout head

e. info@keymer.co.uk

t. 01427 871200

w. keymer.co.uk



¹ Clay tiles are subject to small variations in size because of drying and firing shrinkage in the manufacturing process. Before deciding on the batten gauge and linear coverage, the roof tiler should inspect each batch of tiles to ensure that the correct minimum headlap and sidelap are achieved. Unless otherwise stated, data is based on the tiles laid at minimum headlap.

Tile Fixing - For information please contact the Keymer team.